


HOTRUN X6 1-PHASE WATER HEATERS

Ideal use for HAND WASH BASIN or KITCHENETTE

Power (kWatt) for Installer to select	2.8 kW	3.8 kW	4.8 kW	6.0 kW
Single-Phase power connection	12 Amps	16 Amps	20 Amps	25 Amps
Performance Δ T = 25°C	Flowrate 1.8 L/min	Flowrate 2.3 L/min	Flowrate 2.8 L/min	Flowrate 4.0 L/min
No. of Hand Wash Basins	1	1	1	2
No. of Kitchenette				1
Dimensions	315 x 204 x 130 mm			
Voltage	1x240 V			
IP rating	IP24			
Connection	1/2" BSP			
Weight	3 kg			
Pressure rating	Maximum 1 MPa (tested at 2 MPa)			



HOTRUN X11 1-PHASE & 2-PHASE WATER HEATERS

Ideal use for KITCHEN SINK or with one SHOWER

Power (kWatt) for Installer to select	6.0 kW	7.6 kW	9.6 kW	11 kW
Single-Phase power connection	1 x 25 Amps	1 x 32 Amps	1 x 40 Amps	1 x 50 Amps
Two-Phase power connection	2 x 12.5 Amps	2 x 16 Amps	2 x 20 Amps	2 x 25 Amps
Performance Δ T = 25°C	Flowrate 4.0 L/min	Flowrate 5.0 L/min	Flowrate 6.0 L/min	Flowrate 7.0 L/min
No. of Hand Wash Basins, or	1	2	2 to 3	3
No. of Showers, or	1 *in climate zone 1 & 3	1 *in climate zone 1 & 3	1 *in climate zone 1, 2, & 3	1
No. of Hairdresser Basins, or	1 *in climate zone 1 & 3	1 *in climate zone 1, 2 & 3	1 *in climate zone 1, 2 & 3	1
No. of Kitchenette, or	1	1	1	1, *2 in climate zone 1, 2, & 3
No. of Kitchen Sinks, or	1 *in climate zone 1, 2 & 3	1 *in climate zone 1, 2, & 3	1	1, *2 in climate zone 1, 2, & 3
Dimensions	315 x 204 x 130 mm			
Voltage	1 x 240 V or 2 x 240 V			
IP rating	IP24			
Connection	1/2" BSP			
Weight	4 kg			
Pressure rating	Maximum 1 MPa (tested at 2 MPa)			



HOTRUN X24 3-PHASE WATER HEATERS

Ideal to serve simultaneously: 3-7 HAND WASH BASINS, 1-3 SHOWERS,
1-3 HAIRDRESSER BASINS and/or 1-3 KITCHEN SINKS

Power (kWatt) for Installer to select	12 kW	18 kW	24 kW
Three-Phase power connection	3 x 16 Amps	3 x 25 Amps	3 x 35 Amps
Performance Δ T = 25°C	Flowrate 8.0 L/min	Flowrate 11 L/min	Flowrate 14 L/min
No. of Hand Wash Basins	3	5	7
No. of Showers	1	2	2, *3 in climate zone 1, 2, & 3
No. of Hairdresser Basins	1	2	3
No. of Kitchen Sinks	1	2	3
Dimensions	480 x 243 x 120 mm		
Voltage	415 V		
IP rating	IP24		
Connection	1/2" BSP		
Weight	6 kg		
Pressure rating	Maximum 1 MPa (tested at 2 MPa)		



*For climate zones please refer to the ABCB climate zone map: <https://www.abcb.gov.au/resources/climate-zone-map>