

Hotrun X11



Ideal use for Kitchen Sink or a Shower

Single or 2-Phase power connection is possible

Dimensions	315 x 204 x 130 mm	
Power	6.0 kW / 7.6 kW / 9.6 kW / 11 kW	
Voltage	1 x 240 V or 2 x 240 V	
Current	1-Phase: 25 / 32 / 40 / 50 Amps	
	2-Phase: 2 x 16 / 2 x 20 / 2 x 25 Amps	
IP rating	IP24	
Connection	1/2" BSP	
Weight	4 kg	
Performance (at $\Delta T = 25^{\circ}\text{C}$) (Voltage needs to be 240V)	Set to 6.0 kW	Flowrate 3.6 L/min
	Set to 7.6 kW	Flowrate 5.0 L/min
	Set to 9.6 kW	Flowrate 6.0 L/min
	Set to 11 kW	Flowrate 7.0 L/min
Pressure rating	2MPa	

Variable programmable power setting, 6.0, 7.6, 9.6 and 11 kWatt

Variable programmable temperature limiter can be set & locked to any required temperature limits between 25°C and 60°C

Variable temperature setting by the end user (below limiter temperature)

Tip: Allow 100mm on sides for cord etc and 100mm top and bottom for water connections to allow the cover to be opened after installation

Tip: Base your model & power selection on the winter inlet water temperature

Tip: Position within 6 metres of outlet if possible to minimise legionella risk



Features

1. Pressure resistant up to 2MPa (leak free guarantee for 10 years)
2. Variable power supply selection (kW)
3. Remote life time monitoring option for reporting and full diagnostics
4. Highly energy efficient and will only use exact amount of power required
5. Remote temperature control
6. Built in temperature limiter
7. Size of an A4 piece of paper
8. Digital temperature control and display
9. 10 year warranty with option for service agreement